


Features: Power Supply DR-30

Universal AC input / full range
 Installed on DIN rail TS35 / 7.5 or 15
 Isolation Class II
 LED indicator for power on
 Cooling by free air convection
 100 % full load burn - in test
 3 years warranty



Specifications:

[TOP](#)

Parameter	Description/SPEC.:
Input Voltage	85 ~ 264 VAC ; 124 ~ 370 VDC
Inrush Current	cold start, 27A at 115 VAC, 36A at 230 VAC
DC adjust range	± 10 % rated output voltage
Protections	Short circuit, OLP, OVP
O.L.P.	105 % ~ 160 % constant current limiting, Auto recovery
O.V.P.	115 % ~ 135 % rated output voltage
Setup, rise, hold up time	1000ms, 60ms, 30ms at full load and 230 VAC
Withstand Voltage	I/P-O/P: 3K VAC, I/P-FG: 1.5K VAC, 1min.
Working temp.	-20 ~ 50 °C @ 100 %, 60 °C @ 80 % load
Safety standard	UL 60950-1, TUV EN 60950-1 approved
Approvals	UL, CUL, TUV, CB, CE
EMC standard	EN55022 class B, EN61000-3-2,3, EN61204-3
	EN61000-4-2,3,4,5,6,8,11, ENV50204, EN61000-6-2
Connection	I/P: 2 Poles, O/P: 4 poles screw DIN terminal
Weight/packing	0.27 kg ; 48 pcs / 14.0 kgs / 1.02 CUFT

Model List:



No.	Model	Input	Output	I _{omin}	I _{omax}	Load Reg.	Power
1.	DR-30-12	85~264 VAC	+ 12.00VDC	.00A	2.00A	±1.00%	30.000(w)
2.	DR-30-15	85~264 VAC	+ 15.00VDC	.00A	2.00A	±1.00%	30.000(w)
3.	DR-30-24	85~264 VAC	+ 24.00VDC	.00A	1.50A	±1.00%	30.000(w)
4.	DR-30-5	85~264 VAC	+ 5.00VDC	.00A	3.00A	±2.00%	30.000(w)