

# PM207W

7" TFT 1024x600  
Industrial Touch Monitor



## Ordering Information

PM207WC	7" 1024x600 w/ Capacitive touch
PM207WR	7" 1024x600 w/ Resistive touch
PM207WN	7" 1024x600 w/o touch

## Hardware

- 1080P HDMI, VGA, DVI
- 1 x Line-out/ Mic-in, 2 x built-in Speakers
- OSD Control on rear top cover
- 12~24V DC, < 20 watts

## Display & Touch

- 7" TFT-LCD, 1024x600
- Brightness 250 (cd/m<sup>2</sup>)
- View angle 160/160 (H°/V°)
- Backlight Lifetime 50,000 hours
- Contrast 1000:1
- Capacitive/Resistive touch/No Touch

## Mechanical

- Dimension 225 (W) x 160.7 (H) x 59.0 (D) mm
- Net weight 1.7 (Kgs)
- Cut-out 210.9 (W) x 146.5 (H)
- Panel Mount, VESA 75x75/100x100
- Aluminum front bezel and chassis (Black color)

## Environmental

- IP65 Front
- Op. Temp -10°C ~ 50°C
- Storage Temp. -20°C ~ 70°C
- 10% to 90% @ 40°C (non-condensing)
- CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

